RKL Kaamoskaadot 2025



15

5

Oil Pattern Distance: 43 Feet
Forward Oil Total: 11,12 mL
Forward Boards Crossed: 278 Boards

Reverse Brush Drop: 43 Feet
Reverse Oil Total: 10,76 mL
Reverse Boards Crossed: 269 Boards

Oil Per Board: 40 uL
Volume Oil Total: 21,88 mL
Total Boards Crossed: 547 Boards

	Start	Stop	Loads	Speed	Crossed	Start	End	Feet	T.Oil
1 2	2L	2R	1	14	37	0.0	0.0	0.0	1480
2 (6L	6R	1	14	29	0.0	1.9	1.9	1160
3 8	8L	8R	2	14	50	1.9	5.8	3.9	2000
4	10L	10R	3	18	63	5.8	13.4	7.6	2520
5	12L	12R	3	18	51	13.4	21.0	7.6	2040
6	14L	14R	3	22	39	21.0	30,3	9.3	1560
7	16L	16R	1	22	9	30.3	33,4	3.1	360
8 2	2L	2R	0	22	0	33,4	38.0	4.6	0
9 2	2L	2R	0	22	0	38.0	40.0	2.0	0
10 2	2L	2R	0	22	0	40.0	43.0	3.0	0


Conditioner:
Type In or Select
One
TransferType:
Type In or Select
One

Forward

Reverse

Combined

Buff



|--|

	Start	Stop	Loads	Speed	Crossed	Start	End	Feet	T.Oil
1	2L	2R	0	30	0	43.0	33.0	-10.0	0
2	15L	15R	1	18	11	33.0	30.5	-2.5	440
3	13L	13R	3	18	45	30.5	22.9	-7.6	1800
4	11L	11R	3	18	57	22.9	15.3	-7.6	2280
5	9L	9R	3	18	69	15.3	7.7	-7.6	2760
6	7L	7R	1	14	27	7.7	5.8	-1.9	1080
7	6L	6R	1	14	29	5.8	3.9	-1.9	1160
8	5L	5R	1	14	31	3.9	2.0	-1.9	1240
9	2L	2R	0	14	0	2.0	0.0	-2.0	0

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	MIddle: Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	10,38	2,08	1,06	1,06	2,08	10,38

